

CLAIMS

What is claimed is:

1. An apparatus comprising:

5 a driven element including a housing having an outer surface, the outer surface having a first raised portion and a first non-raised portion, the first non-raised portion at least partially surrounding the first raised portion, the first raised and first non-raised portions defining a first surface pattern;

a driving element operably coupled to the driven element; and

10 a shield coupled to the driving element such that the shield at least partially covers at least one of the driven element and the driving element, the shield having an outer surface, the outer surface having a second raised portion and a second non-raised portion, the second non-raised portion at least partially surrounding the second raised portion, the second raised and second non-raised portions defining a second surface pattern substantially similar to the first surface
15 pattern.

2. An apparatus as set forth in claim 1 wherein the driven element housing is a first housing and wherein the driven element further includes a strainer having a second housing, the first surface pattern located substantially on an outer surface
20 of the second housing.

3. An apparatus as set forth in claim 1 wherein the driven element housing is a first housing and wherein the driven element further includes an air filter having a second housing, the first surface pattern located substantially on an outer surface
25 of the second housing.

4. An apparatus as set forth in claim 1 wherein the driven element is a pump.
5. An apparatus as set forth in claim 1 wherein the driving element is an
5 electric motor.
6. An apparatus as set forth in claim 1 wherein the apparatus further
comprises a conduit box coupled to the driving element, the conduit box having a
base, and at least one wall, the base and wall partially defining a space, the space
10 having an open side opposite the base, and
wherein the shield is coupled to the conduit box.
7. An apparatus as set forth in claim 6 wherein the conduit box base, at least
one wall, and the shield fully define and surround the space.
- 15 8. An apparatus as set forth in claim 6 wherein the apparatus further
comprises at least one fastener, and wherein the at least one fastener couples the
shield to the conduit box.
- 20 9. An apparatus as set forth in claim 8 wherein the at least one fastener is a
screw.
10. An apparatus as set forth in claim 6 wherein the apparatus further includes
25 an alignment member coupled to the shield, and

wherein the alignment member engages the conduit box to properly align the shield and the driving member.

11. An apparatus as set forth in claim 10 wherein the alignment member is
5 integrally formed with the shield.

12. An apparatus as set forth in claim 10 wherein the alignment member is a continuous lip sized and shaped to surround the conduit box.

13. An apparatus comprising:
- a pump including a first housing;
 - a strainer including a second housing, at least one of the first and second housings having a first plurality of indentations that define a first pattern;
 - 5 a motor coupled to the pump in a driving relationship;
 - a conduit box coupled to the motor, the conduit box having a base, at least one wall, and an open side defined by the wall and opposite the base;
 - a shield including an outer surface, the outer surface having a second plurality of indentations that define a second pattern, the second pattern being
 - 10 similar to the first pattern; and
 - at least one fastener coupling the shield to the conduit box such that the shield covers the open side of the conduit box and at least partially covers at least one of the pump and the motor.
- 15 14. An apparatus as set forth in claim 13 wherein the first plurality of indentations are substantially parallel to one another, and
- wherein the second plurality of indentations are substantially parallel to one another.
- 20 15. An apparatus as set forth in claim 14 wherein the first plurality of indentations is parallel to the second plurality of indentations.
16. An apparatus as set forth in claim 13 wherein the at least one fastener is a single screw.

25

17. An apparatus as set forth in claim 13 wherein the apparatus further comprises an alignment member coupled to the shield, and

wherein the alignment member engages the conduit box to properly align the shield and the motor.

5

18. An apparatus as set forth in claim 17 wherein the alignment member is integrally formed with the shield.

19. An apparatus as set forth in claim 17 wherein the alignment member is a

10 continuous lip sized and shaped to surround the conduit box.

20. An apparatus comprising:

a pump including a first housing;

a strainer coupled to the pump, the strainer including a second housing, at least one of the first and second housings having a first raised portion and a first non-raised portion, the first non-raised portion at least partially surrounding the first raised portion, the first raised portion and first non-raised portion defining a first surface pattern;

a motor operatively coupled to the pump;

a conduit box coupled to the motor, the conduit box having a base, at least one wall, and an open side defined by the wall and opposite the base;

a shield including an outer surface, the outer surface having a second raised portion and a second non-raised portion, the second non-raised portion at least partially surrounding the second raised portion, the second raised and second non-raised portions defining a second surface pattern; and

at least one fastener coupling the shield to the motor such that the shield at least partially covers at least one of the pump and the motor.

21. An apparatus as set forth in claim 20 wherein the apparatus further includes an alignment member coupled to the shield, and

wherein the alignment member engages the conduit box to properly align the shield and the motor.

22. An apparatus as set forth in claim 21 wherein the alignment member is integrally formed with the shield.

23. An apparatus as set forth in claim 21 wherein the alignment member is a continuous lip sized and shaped to surround the conduit box.

24. An apparatus comprising:
- a motor;
 - a conduit box coupled to the motor, the conduit box having a base, at least one wall, and an open side defined by the wall and opposite the base;
- 5 a shield coupled to the conduit box and being sized to cover the open side of the conduit box and at least partially cover the motor; and
- a fastener, the fastener being the sole attachment between the shield and the conduit box.
- 10 25. An apparatus as set forth in claim 24 wherein the apparatus further includes an alignment member coupled to the shield, and
- wherein the alignment member engages the conduit box to properly align the shield and the motor.
- 15 26. An apparatus as set forth in claim 25 wherein the alignment member is integrally formed with the shield.
27. An apparatus as set forth in claim 25 wherein the alignment member is a continuous lip sized and shaped to surround the conduit box.
- 20 28. An apparatus as set forth in claim 24 wherein the fastener is a screw.